

## Dual User Timed Shot Dispensing Station

## Product Description

A pneumatic timed dispensing system for low to medium viscosity fluids, adhesives, and liquids. Benchtop system with dual outlet shot valves allowing 2 independent stations to operate from the same main pressure pot system. Fill the 5-litre stainless steel pressure pot, attach the feed tube fluid line. Set the time on the dispenser. Press the foot switch for a measured deposit. No drips, no mess, no waste.

## Typical Applications

Use this system for making repeat, timed deposits or controlled beads of Cyanoacrylate adhesives, UV cure adhesives, primers, activators, solvents, inks, oils, PVA glue, lubricants and many other materials.

## Health & Safety in Use

This system will reduce exposure to fumes as the adhesive is kept with a sealed pressure pot and fluid lines. As the valves accurately control deposits, there is less opportunity for contamination, mess and material waste. All systems are certified for industrial use and are CE approved.



## Specifications

122-2250-2	Complete Dual Valve System
Tank Size:	5 Litre
Tank Part:	TS2250
Dispenser Part:	TS9150
Valve Part:	TS1212
Tank Pressure:	75 PSI
Dispense Time:	0.01 to 30 second adjustable or manual
Valve Pressure:	1 to 60 PSI adjustable
Manifold:	Delrin material for up to 4 valves
Activation:	Foot switch manual control
Details:	CE approved, 1 Year warranty

## Options

Systems are available for single user, 3 users or 4 users. Pressure pots are available in sizes ½ litre, 2 litre or 10 litre. Dispensers are available with digital timers, memory storage and self-repeat timers.

## Requirements

All systems require a compressed air feed of around 70-100 PSI and power voltage of 110-220V AC.

## Lead Time

These systems are available in 24-72 hours from order.

## Warranty

All equipment is covered by a 1 Year warranty. The TS9150 dispenser is covered by a 2 Year warranty.

## Benefits

- Fast Repeat Shots eliminate guesswork
- Reduces adhesive waste
- Adds consistency to assembled parts
- Eliminates exposure to fumes
- Reduces operator hand fatigue
- Saves assembly time
- CE approved parts

The data, information and values contained in this Technical Data Sheet have been obtained by specific tests conducted in a controlled environment, and should be used for guidance purposes only. Although we believe them to be reliable and accurate, users should always conduct their own tests in their specific working conditions to ensure that the product is suitable and effective for use. It is the user's sole responsibility to determine the suitability of the product for the application. Adhesive Dispensing Ltd cannot be held responsible for the results of procedures undertaken elsewhere, nor for the safeguarding of personnel or property, all of which is the duty of the user. Suitability of products or methods is discretionary. Therefore, warranties or implied usage obligations should not be attributed to, and are not the responsibility of, Adhesive Dispensing Ltd. Adhesive Dispensing Ltd are not liable for any financial loss or other damages incurred by the user as a result of the use of this product. Product dimensions and design are approximate and could be subject to change, without notice.