

PRODUCT SHEET

Part TTN20 Tapered Tip 20 Gauge

Product Description

High quality industrial smooth flow tapered tips in 20 gauge bore size. Made in polyethylene 1.25" (38.1mm) long. Double helix luer locking design hub. Inner diameter of 0.024" (0.61mm). Silicone free and industrial grade safe to 100 psi. Supplied in packs of 50 or bulk packs of 1000.

Typical Applications

Use these tapered tips for making controlled dots and beads of many materials, especially thick pastes, gels silicones, RTVs, sealants, fluxes, grease and UV cure adhesives. Can be used with all luer lock and luer slip syringe barrels, dispensing bottles and dispensing valves.



Components are available to order direct from stock. Products are of the highest quality and compatible with most dispensing systems and valves. Supplied in sealed boxes with labels and batch codes.

Part Numbers

Part TTN20	20G Tip Box of 50
Part TTN20-500	20G Tip Pack/500
Part TTN20-1000	20G Tip Pack/1000

The data, information and values contained in this Technical Data Sheet have been obtained by specific tests conducted in a controlled environment, and should be used for guidance purposes only. Although we believe them to be reliable and accurate, users should always conduct their own tests in their specific working conditions to ensure that the product is suitable and effective for use. It is the user's sole responsibility to determine the suitability of the product for the application. Adhesive Dispensing Ltd cannot be held responsible for the results of procedures undertaken elsewhere, nor for the safeguarding of personnel or property, all of which is the duty of the user. Suitability of products or methods is discretionary. Therefore, warranties or implied usage obligations should not be attributed to, and are not the responsibility of, Adhesive Dispensing Ltd. Adhesive Dispensing Ltd are not liable for any financial loss or other damages incurred by the user as a result of the use of this product. Product dimensions and design are approximate and could be subject to change, without notice.

Technical Information

Part Codes	TTN20, TN20 or AD20TT
Colour	Pink
Max Fluid Pressure	Up to 100 psi
Construction	Polyethylene
Length	1.25" (38.1mm)
Tip End ID	0.024" (0.61mm)
Connection	Luer Lock. Double Helix Thread

Packaging

Tips are supplied in boxes of 50 or bulk packs of 500 or 1000. Packs are sealed and include detailed labels with batch code numbers.

Pricing and Lead Times

Our tips are very competitively priced. We hold extensive stocks and ship for next day UK deliveries by courier. For overseas customers, we use TNT, DHL or FedEx tracked.

Options

This tip is also available with a softer grade low density PE plastic. Part Code TT20-DHUV.

Health & Safety in Use

Tips are safe to 100 psi and silicone free, reducing risk of operator contact with the materials being dispensed and contamination of adhesives placed inside.

Features

- Safe to 100 psi pressure
- Compatible with most liquids & gels
- Silicone free plastics
- UV filter plastic hub
- Smooth flow design for pastes
- Double helix luer locking hub
- Supplied in sealed packs
- High quality product
- Available direct from stock